# **Product information**

# TEADIT O5/02102012

### **TEADIT 24 HD**

#### **Material properties:**

**TEADIT 24 HD** is a non-asbestos gasket material made from expanded, pre-densified, pure virgin PTFE. The whole production process is subject to strict quality control, registered under DIN EN ISO 9001

Please note: the colour of the actual product might vary from the image on this data-sheet

#### Application areas:

**TEADIT 24 HD** is particularly well suited to compensate for out-of-parallel and/or damaged sealing surfaces, and where a certain remaining thickness is required. Typical applications are heat exchangers, large containers, tank lids, pump housings, flanges, hand- and manholes, etc.



- Temperature range: 240°C up to +260°C, for short periods up to +310°C
- Chemical resistance: resistant against all chemicals from pH 0-14 (except molten alkali metals and elemental fluorine at high temperature and pressure)
- Pressure resistance: vacuum up to 200 bar
- Density: 1,0 g/cm3, +/- 0,1g/cm3
- Aging resistance: TEADIT 24 HD does not age (please note: adhesive tape has limited shelf life!)
- Colour: white

#### Advantages:

- Quick and simple installation: adhesive strip makes installation easier
- Excellent malleability: compensates for small damages and uneven areas on the flange faces
- Exceptional thermal and chemical stability: makes this material very versatile
- No risk: the versatility of Teadit 24 HD eliminates the risk of using wrong material for a certain application – this prevents avoidable breakdowns
- **TEADIT 24 HD** is physiologically harmless. It has no smell or taste. It is neither contaminating nor toxic and does not get influenced by micro-organisms and / or fungi.



#### Standard dimensions:

Dimensions (mm) Standard flange size

4 x 2,5 up to DN 500
6 x 4,6 from DN 500 up to DN 1500
8 x 5,5 DN 1500 and larger
10 x 7 DN 1500 and larger

When choosing the best suitable dimension of **TEADIT 24 HD**, one has to take the available bolt torque and possibly damaged and / or out-of-parallel gasket surfaces into account.

**TEADIT 24 HD** is available on spools, with self-adhesive strip

## Approvals:

• WRc





TEADIT INTERNATIONAL - Rosenheimer Str. 10, 6330 Kufstein, AUSTRIA Tel.: +43-5372-64020-0, Fax: +43-5372-64020-20 austria@teadit.eu - www.teadit.eu